



**Retract**

**"The Ultimate Floor Stripper"**

(Heavy Duty Floor Finish Stripper Concentrate)

- **Fast Acting**
- **No Ammonia Odor**
- **Rinse Free Formula**


Retract is a super concentrated rinse free floor finish stripper. This unique formula is free of Ammonia and Caustic. Retract is fast penetrating and simple to use. Retract has been designed to be especially effective on today's finishes which have been hardened due to high speed burnishing. Retract rapidly penetrates multiple layers of finish build up. Retract works great on hard to remove sealers as well.

Typical Properties:

-----	
Activity .....	100%
Evaporation Rate .....	Slower than Butyl
Pounds per Gallon .....	8.0-8.1
pH (ASTM E70) .....	11.0 - 12.5
End Use Coverage (At Dilution).....	Strips 1000 - 2000 Ft <sup>2</sup>
Freeze Thaw (ASTM D3209) .....	Passes
Solubility in Water.....	Complete
Alkali Residue .....	None

**End User Dilutions:** Dilute 1 gallon of Retract with 10 gallons of water for normal stripping. Use 1:5 for heavy duty stripping and 1:20 for light stripping or deep scrubbing.

# Material Safety Data Sheet



## Section I Company Information

Product Name: Retract  
Company Name: Liquid Solutions Of America  
Address: 2155 Stonington Avenue, Hoffman Estates, IL. 60195  
Phone: 630-855-8010  
Emergency Phone: 630-247-0801

Proper Shipping Name: Ethanolamine Solutions  
Identification No: UN 2491  
Hazard Class: Class 8  
Generic Description: Cleaning Compound

## Section II Hazardous Ingredients

CAS No	Ingredient	%	TLV
141-43-5	Ethanolamine	10-30	3 ppm
26027-38-3	Nonionic Surfactant	2-5	
111-76-2	2-Butoxyethanol	10-50	25 ppm
107-21-1	Ethylene Glycol	0-20	

## Section III Physical Data

Boiling Point: 212 F                      Specific Gravity: 0.987  
Vapor Pressure: Not Determined      Percent Volatiles: N/A  
Vapor Density: Less than Air          H2O Solubility: Complete  
Evaporation Rate: Slower than n-Butyl Acetate  
Appearance & Odor: Clear Solution, Typical Mild odor

## Section IV Fire & Explosion Data

Flash Point: None  
Extinguishing Media: Foam or carbon dioxide or dry chemical.  
Firefighting Procedure: Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires.

## Section V Health Hazard Data

Routes of Entry: Inhalation, Skin & Ingestion  
Eyes: Can cause mild to moderate irritation.  
Skin: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.  
Breathing: Excessive inhalation of vapors can cause nasal and respiratory irritation.  
Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.  
**First Aid Procedures:**  
Eyes: Irrigation of the eye immediately with water for ten minutes is good safety practice.  
Skin: Wash off in flow water or shower. Wash clothing before reuse.  
Inhalation: Remove to fresh air if effects occur. If respiration stops, give mouth-to-mouth resuscitation. Administer oxygen if available. Call physician and/or transport to medical facility.  
Ingestion: Seek medical attention. Unless advised otherwise, induce vomiting by giving either syrup of ipecac followed by 2 glasses of water or by sticking finger down throat. Do not give anything by mouth if the person is drowsy, unconscious or has no gag reflex.

## Section VI Reactivity Data

Hazardous Polymerization: Will not occur  
Stability: Stable  
Incompatibility: Avoid strong oxidizing agents.

## Section VII Spill & Leak Procedures

Response to spills: Stop discharge, if it can be performed safely, and contain material. If a substantial quantity is spilled, recover with pump or vacuum. Otherwise, use an absorbent material. Place contaminated material in a suitable container for disposal. Do not flush to sewer, stream or other bodies of water.

## Section VIII Protective Equipment

Respiratory Protection: If TLV of the product or any component is exceeded, a NIOSH/MSHA jointly approved air supplied respirator is advised. Engineering or administrative controls should be implemented to reduce exposure.  
Ventilation: Provide sufficient ventilation to maintain exposure below TLV(s).  
Protective Gloves: Wear chemical resistant gloves such as nitrile rubber.  
Eye Protection: Chemical splash goggles are advised.  
Other Protective Equipment: Wear impervious clothing and boots.

## Section IX Special Precautions

Precautions to be taken in Handling and storage: Handle with reasonable care. Avoid breathing vapors. Store in a cool dry place. Dispose of empty containers in accordance with local, state and federal guidelines. This product contains 2-Butoxyethanol & Ethylene Glycol which are subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

## Warranty Information - Please Read Carefully:

Liquid Solutions Of America believes that the information in this literature is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application to determine its performance, efficacy and safety. Liquid Solutions Of America provides the sole warranty that the product will meet our current sales specifications. Your exclusive remedy and Liquid Solutions Of America only liability for breach or warranty is limited to refund of the purchase price or replacement of any product shown to be other than as warranted, and Liquid Solutions Of America expressly disclaims any liability for incidental or consequential damages.



Ethanolamine Solution  
CLASS 8, UN 2491, PACKAGING GROUP III